Product overview



POWERSWITCH

Reliable solid-state switching devices for frequent switching

DOLD

Our experience. Your safety.

Reliable solid-state switching devices from DOLD

POWERSWITCH

Always safe and reliable switching - with the POWERSWITCH series you get solid-state switching devices with real added value.

DOLD has been developing and producing solid-state switching devices for industrial switching technology for decades. Thanks to the extensive portfolio from a single source, DOLD solid-state relays / contactors offer the possibility of switching loads in a wide variety of areas.

Plug-in, connect, done!
The ready-to-use design, thanks to the optimally adapted heat sink, allows quick and easy commissioning in just a few steps.

High switching frequencies, long service life
Wherever high switching frequencies and cycles are required, our solid-state switching devices are the ideal solution. Once installed, the devices remain operational for an almost infinite period of time. Regular time- and cost-intensive device replacement is thus saved.

Wear-free and noiseless switching
The POWERSWITCH series is characterized by wear-free and noiseless switching and is capable of safely and reliably withstanding repeated loads and high temperatures. This makes our solid-state switching devices particularly suitable for use in medical applications and stage technology.

DCB - Technology

DCB Technologie

The DCB technology (Direct-Copper-Bonding-Process) ensures very good heat transfer properties.



Fields of application

- Heating controls
- Hot glue robots
- Soldering lines
- Tapping systems
- Pumps
- Photocopying machines
- Automat construction
- Extruder plants
- Injection molding machines
- Furnace controls
- Three-phase motors
- Lighting controls
- Funding agencies
- Packaging machinery

High switching frequencies, long service life with minimum overall width

POWERSWITCH - Your advantages at a glance:

Long service life
Long service life for high system availability and low maintenance costs

Noiseless operation
Since no mechanical components are present, the switching process is noiseless

High switching frequencies
Wear-free switching is reliably possible even at high switching frequencies

Ready to use
Ready for immediate use thanks to optimally adapted heat sink

Minimum overall width
The compact design allows a space-saving installation

High temperatures
Reliable switching even under the most difficult environmental conditions

1-, 2- and 3-pole versions
For switching 1-, 2- or 3-phase loads up to 600 V

Version ohmic loads
The „zero point switching“ method is used to switch ohmic loads

Version inductive loads
For inductive loads the „switching at voltage maximun“ version is suitable

Load monitoring
For detection of over- and undercurrent in alternating current networks

Extreme environmental conditions
Vibration and shock resistant for use even under the most difficult environmental conditions

Fast commissioning
Flexible wiring and fast commissioning as well as simple snap-on option on DIN top-hat rail



Solid-state relay PH 9270

More functionality, more possibilities
Solid-state relay / contactor

Solid-state relays of the **POWERSWITCH** series are ideally suited for mounting on existing cooling surfaces and allow fast and simple mounting with just two screws. With a narrow width from 17.5 mm, the solid-state relays are absolutely space-saving.

The DCB technology (Direct-Copper-Bonding-Process) ensures very good heat transfer properties. Depending on the property of the heat sink, continuous currents of up to approx. 90 A are possible. If a large number of resistive loads have to be switched, the solid-state relays can be mounted on a collective heat sink.

Depending on the application, it is recommended to protect the solid-state relays against short circuits with special fuses.

The solid-state relays offer a wide range of applications, e.g. in injection moulding machines in the plastics and rubber industries, in packaging machines, soldering systems and in the food industry.

Solid-state contactors of the **POWERSWITCH** series consist of a solid-state relay plus an optimized heat sink and are therefore ready for immediate use. Depending on the version, currents of up to 50 A are permitted.

Like all solid-state switching devices, the solid-state contactors also impress with their narrow and space-saving design. Thanks to the pre-dimensioned heat sink, the devices can easily be snapped onto a DIN rail or mounted on carrier plates using fastening screws.

Overview	AC loads				
					
Device type	RK 9260	PK 9260	PK 9261	PH 9260.91/042	PH 9260.91
Classification	**Solid-state relay 1-pole**	**Solid-state relay / contactor 1-pole**	**Solid-state relay / contactor 1-pole**	**Solid-state relay / contactor 1-pole**	**Solid-state relay / contactor 1-pole**
Load voltage	**AC 280, 480, 600 V**	**AC 240, 480, 600 V**	**AC 480, 600 V**	**AC 480 V**	**AC 240, 480, 600 V**
Peak reverse voltage	**AC 650, 1200, 1600 V**	**AC 650, 1200, 1600 V**	**AC 1200, 1600 V**	**AC 1200 V**	**AC 1200, 1600 V**
Load current	5 A	**25, 35, 50, 72, 88 A 10, 15, 20, 30, 40, 50, 88 A with heat sink**	**7,5, 15 A**	**25, 50 A**	**25, 50 A**
Control input	**DC 4 ... 32 V AC 100 ... 230 V**	**DC 4 ... 32 V AC 100 ... 230 V AC/DC 18 ... 30 V**	**DC 4 ... 32 V AC 100 ... 230 V**	DC 4 ... 20 mA	**DC 4 ... 32 V AC/DC 18 ... 36 V AC/DC 100 ... 240 V**
Signal output	—	—	—	—	—
Heat sink	—	**optional**	**optional**	**optional**	**optional**
DIN rail	•	•	•	•	•
Approval	—	UL [1]	—	—	UL [1]
Specification	**for ohmic loads**	**for ohmic loads**	**for motor loads**	**with impulse packet control**	—
Width	**17,5 mm**	**22,5 mm**	**22,5 mm**	45 mm	45 mm


[1] Depending on variant

1-, 2- and 3-pole versions available



Solid-state contactor PK 9260

c UL US LISTED



Your advantages at a glance

- Immediately ready for use - thanks to optimally adapted heat sinks
- Long service life for high system availability
- Noiseless and wear-free switching
- Simple mounting on the heat sink
- Easy integration into existing automation systems
- Compact design from 17.5 mm overall width
- 1-, 2- and 3-pole versions available
- Use even under extreme environmental conditions (vibration and shock resistant)

				DC loads
				
PH 9270.91/003	PH 9270.91	PH 9260.92	PI 9260.92 /.93	PK 9265
Solid-state relay / contactor 1-pole	Solid-state relay / contactor 1-pole	Solid-state relay / contactor 2-pole	Solid-state relay / contactor 2-, 3-pole	Solid-state contactor 1-pole
AC 240 V	AC 480 V	AC 240, 480 V	AC 240, 480, 600 V	DC 60, 300 V
AC 800, 1200 V	AC 1200 V	AC 1200 V	AC 650, 1200, 1600 V	DC 100, 600 V
25, 45 A	40 A	2 x (32, 48 A)	20, 30, 50, 60 A 2 x (20, 30 A) with heat sink 3 x 20 A with heat sink	25, 10 A
DC 20 ... 32 V	DC 20 ... 32 V	DC 18 ... 30 V	DC 10 ... 32 V AC 100 ... 230 V	DC 4 ... 32 V
0 ... 10 V	—	—	—	—
optional	optional	optional	optional	•
•	•	•	•	•
—	—	—	—	—
with load circuit monitoring and analogue output	with load circuit monitoring and PNP semiconductor output	—	2- or 3-phase controlled version	for ohmic and inductive loads
45 mm	45 mm	45 mm	67,5 mm	22,5 mm

Solid-state contactors, also with load monitoring

The **solid-state contactors** of the **POWERSWITCH** series are particularly suitable for installation in switch cabinets due to their simple snap-on mounting on the DIN rail and are available in 1-, 2- and 3-pole versions. Optionally up to 3 separate solid-state contactors in one device.

The devices are characterized by a compact and space-saving design and allow fast mounting by snapping onto the DIN rail. Due to the ready-to-use design, the devices are immediately ready for use.

With the device characteristics „zero point switching“ or „instantaneous switching“ you are equipped for all applications with AC loads.

Whether current monitoring, load control or analogue control, the solid-state contactors offer a wide range of applications, such as switching motors, heaters, valves or lighting. Special solid-state contactors can also monitor the load circuit.

The solid-state contactors operate in a load voltage range of up to 600 V and, thanks to the wide control voltage range, can be operated with a PLC or simple temperature controllers. The devices cover a current range up to 90 A with only a few versions.

Overview

				
Device type	BF 9250/001	BF 9250/003	BF 9250/008	
Classification	**Solid-state contactor 1-, 2-, 3-pole**	**Solid-state contactor 2-, 3-pole**	**Solid-state contactor 1-, 2-, 3-pole**	
Load voltage	**AC 480 V**	**AC 480 V**	**AC 240, 480 V**	
Peak reverse voltage	**AC 1200 V**	**AC 1200 V**	**AC 1200 V**	
Load current	**10, 25, 50 A 2 x (6,5, 15, 25 A) 3 x (5, 10, 15 A)**	**2 x (6,5, 15, 25 A) 3 x (5, 10, 15 A)**	**10, 25, 50 A 2 x (6,5, 15, 25 A) 3 x (5, 10, 15 A)**	
Control input	**DC 24 V**	**DC 24 V**	**DC 24 V**	
Signal output	•	—	—	
Heat sink	•	•	•	
DIN rail	•	•	•	
Approval	UL	UL	UL	
Specification	**with temperature monitoring (storing)**	**Control inputs galvanically isolated from each other**	**Control via separate terminals (A1/A2)**	
Widths	**22,5, 45, 90 mm**	**22,5, 45, 90 mm**	**22,5, 45, 90 mm**	

Versatile options for individual configuration



Solid-state contactor BF 9250/008

c UL US LISTED

Your advantages at a glance

- Long service life for high system availability
- Noiseless and wear-free switching
- Simple mounting by snapping onto DIN rail
- Easy integration into existing automation systems
- For 1-, 2- or 3-pole loads
- Available with UL approval
- With load circuit monitoring (BH 9251)

						
	BF 9250/004	BF 9250/042	BF 9250/002	BH 9250/001	BH 9250.03/006	BH 9251
	Solid-state contactor 2-, 3-pole	**Solid-state contactor 1-pole**		**Solid-state contactor 1-, 2-, 3-pole**	**Solid-state contactor 3-pole**	**Solid-state contactor 1-pole**
	AC 480 V	**AC 115, 240, 480 V**		**AC 480 V**		**AC 48, 230, 400 V**
	AC 1200 V	**AC 1200 V**		**AC 1200 V**		**AC 1200 V**
	10, 25, 50 A	**2 x (6,5, 15, 25 A) 3 x (5, 10, 15 A)**		**10, 25, 50 A 2 x (6,5, 15, 25 A) 3 x (5, 10, 15 A)**	3 x 3 A 2 x 1 A	**10, 20, 40 A**
	DC 24 V	**0 - 10 V 4 - 20 mA 0 - 10 kΩ**		**DC 24 V**		**AC/DC 9,6 ... 270 V**
	—	—		•	—	•
	•	•		•		•
	•	•		•		•
	UL	UL		UL		—
	Control inputs with common ground	**Output with impulse control**		**with temperature monitoring (storing)**	**additional 2 semiconductor outputs**	**with load monitoring**
	22,5, 45, 90 mm			**45, 67,5, 112,5 mm**		**45, 67,5, 112,5 mm**

Our experience. Your safety.

DOLD - Your solution provider with over 90 years of experience



Hybrid relays - perfectly combined

Hybrid relays combine the advantages of robust relay technology with wear-resistant semiconductor technology in a perfect way.

Classic electromechanical relays offer a significant advantage over solid-state relays. While solid-state relays generate heat permanently due to the forward voltage, which must be dissipated by heat sinks at higher load currents, the current-carrying relay contact has a very low contact resistance and thus generates hardly any heat loss.

Solid-state relays are insensitive to shock and vibration. Their strengths lie above all in the switch-on and switch-off processes. No bouncing, no electric arcs, no mechanical wear - and thus an almost unlimited electrical service life.

The **hybrid relay RK 3070** from DOLD perfectly combines the advantages of both worlds. When switched on, the solid-state first switches in the zero crossing of the alternating voltage. A few milliseconds later, the relay contact takes over the continuous current and ensures low power dissipation. When the relay is switched off, the current is first transferred from the relay to the solid-state, which then switches off at zero current. In this way, surge voltages and currents in the load circuit are minimized.

Due to the combination of the different switching technologies, the RK 3070 is particularly suitable for applications that require a high switching capacity and a long service life at the same time. It is therefore particularly suitable for systems in which a standstill leads to high costs, i.e. the relay should function reliably over as long a period as possible. Such applications can be found in automation technology and the process industry as well as in offshore wind turbines.

Technical features	
Output contacts max.	1 NO
Load voltage	AC 24 ... 280 V
Peak reverse voltage	AC 800 V
Load current	20 A
Control input	AC/DC 24 V AC/DC 85 ... 265 V
Width	17,5 mm

More

Info

E. Dold & Söhne GmbH & Co. KG
Bregstraße 18 • D-78120 Furtwangen
T +49 7723 654-0 • F +49 7723 654-356
dold-relays@dold.com • www.dold.com

BE08 / 0226